


TECHNICAL FEATURES

L004-K01.SC6135.NE2178.EP5 SPLIT DEVICE

	Technical Features	
	453,00	
Production Facility	Turkey	455,00
Brand	Atlas	
Type of casing	With Housing	
Application	-25/45°C	
Refrigerant	R449A	
Cooling Capacity (Watts) (-25/+45°C)	727	
Energy Efficiency (COP)	1,25	1, 000, 0
Body Model	Atlas - 1-CHH-135	
Liquid Line	1/4"	505,00
Suction Line	3/8"	
Insulation	Included	
Condense	r and Fan Information	
Condenser Brand	Karyer	
Condenser Model	Condenser - 1-CHH-135	
Condenser Capacity Watts Dt = 15 °C	3.471	
Condenser Fin Space (mm)	2,10	
Surface Area (m2)	7,9	
Air Flow (m3/h)	1.613	2000
Fan Motor Brand	SANMU	
Fan Motor Model	SANMU YWF (K) 6E 350S-Z 900	
Fan Speed (RPM)	6 Pole(~900 rpm)	
Fan Grill	-	17
Fan Motor (Quantity x Diameter)	1x350	
Fan Motor Input Power (kW)	1x0,103	
Fan Motor Power Sup. (V / Ph / Hz)	220-230/ 1 / 50	
Fluid Line		
Liquid Tank	2SDI - 1/4" L.Tank	
Filter Dryers	Danfoss 023Z455291 DML 032S 1/4" Solder	
Gas Sightglass	Sanhua SYJ06H11 1/4" Solder	
	Controls	Compre
Combined Pressure Control	Danfoss 060-124166 KP15 Presostat	Compressor Brand
Fan Control	Danfoss 061F8333 ACB-2UA305W F.K. 13,0 / 16,0 bar	Compressor Type
Electrical Panel	LBP Elk. Pano	Compressor Model
Low Pressure Manometer	Low Pressure Manometer	Compressor Quantity & Power (Pcs-Hp) 1 x 1,00
High Pressure Manometer	High Pressure Manometer	Compressor Power Sup. (V / Ph / Hz)
·		





Compressor Features		
Compressor Brand	Embraco	
Compressor Type	Hermetic	
Compressor Model	Embraco NEU 2178 GK	
Compressor Quantity & Power (Pcs-Hp) 1 x 1,00		
Compressor Power Sup. (V / Ph / Hz)	220-230/1/50	
Compressor Discharge line (Ø inches)	1/4"	
Compressor Suction line (Ø inches)	3/8"	