


TECHNICAL FEATURES

M135-K07.SC6245.SE6036.ES4 SPLIT DEVICE

	Technical Features	\neg
	General Features	\dashv
Production Facility	Turkey	
Brand Atlas		
Type of casing	With Housing	
Application	-10/45°C	
Refrigerant	R449A	
Cooling Capacity (Watts) (-10/+45°C)	8.804W	
Energy Efficiency (COP)	2,26	
Body Model	Atlas - 7-CHH-245	
Liquid Line	1/2"	
Suction Line	7/8"	\Box
Insulation	Included	
Conde	nser and Fan Information	\neg
Condenser Brand	Karyer	
Condenser Model	Condenser - 7-CHH-245	
Condenser Capacity Watts Dt = 15 °C 19.166		
Condenser Fin Space (mm)	2,10	
Surface Area (m2)	40,7	
Air Flow (m3/h)	6.128	
Fan Motor Brand	SANMU	
Fan Motor Model	tor Model SANMU YWF (K) 6E 450S-Z 900	
n Speed (RPM) 6 Pole(~900 rpm)		
Fan Grill -		
Fan Brackets & Grills	-	
Motor (Quantity x Diameter) 2x450		
Fan Motor Input Power (kW)	2x0,174	
Fan Motor Power Sup. (V / Ph / Hz)	220-230/ 1 / 50	
	Fluid Line	\neg
Rotolock Valve	Included	\neg
quid Tank 6SDI - 1/2" L.Tank		
Filter Dryers	Danfoss 023Z457291 DML 084S 1/2" Solder	
Gas Sightglass	Sanhua SYJ12H11 1/2" Solder	
	Controls	
Combined Pressure Control	Danfoss 060-124166 KP15 Presostat	
Fan Control	Danfoss 061F8333 ACB-2UA305W F.K. 13,0 / 16,0 bar	
Electrical Panel	MBP Elk. Pano	-





Gas Sightglass	Sanhua SYJ12H11 1/2" Solder			
Controls		Compressor Features		
Combined Pressure Control	Danfoss 060-124166 KP15 Presostat	Compressor Brand	Embraco	
Fan Control	Danfoss 061F8333 ACB-2UA305W F.K. 13,0 / 16,0 bar	Compressor Type	Scroll	
Electrical Panel	MBP Elk. Pano	Compressor Model	Embraco SE6036GS-O	
Low Pressure Manometer	Low Pressure Manometer	Compressor Quantity & Power (Pcs-Hp)	1 x 5,00	
High Pressure Manometer	High Pressure Manometer	Compressor Power Sup. (V / Ph / Hz)	380 - 400 / 3 / 50	
		Compressor Discharge line (Ø inches)	1/2"	
		Compressor Suction line (Ø inches)	7/8"	
		Compressor Crank Heater	48cm / 70W / 220V (15-29)	
		Compressor Cover	Included	