
ATLASICS

TECHNICAL FEATURES

M145-K10.SC6250.SE6043.ES4 SPLIT DEVICE

	Technical Features	
General Features		469,00
Production Facility	Turkey	
Brand	Atlas	
Type of casing	With Housing	
Application	-10/45°C	0
Refrigerant	R449A	
Cooling Capacity (Watts) (-10/+45°C)	10.461	
Power Input	4.628	· · · o
Energy Efficiency (COP)	2,26	
Body Model	Atlas - 10-CHH-250	
Liquid Line	1/2"	
Suction Line	7/8"	
Insulation	Included	e
Conde	nser and Fan Information	
Condenser Brand	Karyer	550,00
Condenser Model	Condenser - 10-CHH-250	1
Condenser Capacity Watts Dt = 15 °C	25.216	
Condenser Fin Space (mm)	2,10	The second se
Surface Area (m2)	48,1	-10
Air Flow (m3/h)	8.287	
Fan Motor Brand	SANMU	
Fan Motor Model	SANMU YWF (K) 6E 500S-Z 900	
Fan Speed (RPM)	6 Pole(~900 rpm)	
Fan Grill	-	
Fan Motor (Quantity x Diameter)	2x500	
Fan Motor Input Power (kW)	2x0,300	
Fan Motor Power Sup. (V / Ph / Hz)	220-230/ 1 / 50	
	Fluid Line	
Rotolock Valve	Included	1.00
Liquid Tank	8SDI - 1/2" L.Tank	
Filter Dryers	Danfoss 023Z457291 DML 084S 1/2" Solder	
Gas Sightglass	Sanhua SYJ12H11 1/2"Solder	
	Controls	
Combined Pressure Control	Danfoss 060-124166 KP15 Presostat	Compressor Brand
Fan Control	Danfoss 061F8333 ACB-2UA305W F.K. 13,0 / 16,0 bar	Compressor Type
Electrical Panel	MBP Elk. Pano	Compressor Model
Low Pressure Manometer	Low Pressure Manometer	Compressor Quantity & Power (Pcs-Hp)
High Pressure Manometer	High Pressure Manometer	Compressor Power Sup. (V / Ph / Hz)
		Compressor Discharge line (Ø inches)
		Compressor Suction line (Ø inches)
		Compressor Crank Heater
		Compressor Cover



1 x 6,00

Included

1/2"

7/8"

380 - 400 / 3 / 50 - 60

54cm / 70W / 220V (38-48)